

Application No.: 10/669,621
Amendment dated: October 25, 2005
Reply to Office Action dated: July 25, 2005

AMENDMENT TO THE SPECIFICATION

POLISH CLEANING APPARATUS AND METHOD IN MANUFACTURE OF HGA

Related Application

[0001] This application is a Divisional of Patent Application 09/810,833 filed on March 16, 2001 and issued as patent number 6,645,308 on November 11, 2003.

FIELD OF THE INVENTION

[0002] The present invention relates generally to a cleaning and polishing apparatus and method used in the disk drive industry. More specifically, the present invention relates to a cleaning and polishing apparatus and method used in the manufacture of a head gimbal assembly.

BACKGROUND OF THE INVENTION

[0003] Thin film heads are used for reading or writing data onto a recording layer of a data storage disk. Typically, the head "flies" above the surface of the disk at a very low "altitude". The height of the air gap between the head and the disk is usually measured in fractions of a micron. The low height of the air gap causes an air bearing to be formed.

[0004] For a disk that stores data using magnetic effects, the head usually includes a radio frequency coil for transmitting and receiving a magnetic field to write and read in the recording layer. For disks that store data using optical effects, the head may include an objective lens to focus a light beam at the recording layer.

Substitute Specification Clean Version
75665_1.DOC

Application No.: 10/669,621
Amendment dated: October 25, 2005
Reply to Office Action dated: July 25, 2005

[0005] Along with the evolution of the disk industry, the surface cleanliness of read-write heads has become one of the most critical concerns. With low-flying heads, dust in the environment is a serious problem. Dust particles can cause catastrophic "head crashes" destroying the head and disk. Also, significant amounts of dust can accumulate on the head to interfere with the magnetic or optical effects. Contaminants may cause a disk driver to malfunction or even fail to spin up.

[0006] Classical wash, rinse and dry technology using an aqueous chemical substance and ultrasonic agitation can not provide adequate cleaning efficiency for a head's air bearing surface. More effective contamination removal methods to ensure that components and drives always remain as clean as possible are needed.

[0007] US Patent No. 5,467,238 issued to Neville K. Lee et al. on November 14, 1995, disclosed a cleaning apparatus for cleaning read/write heads used for accessing data stored on a recording disk of a disk drive. The cleaning apparatus had a mounting base positioned adjacent to the disk. The base includes a ratchet mechanism for rotating a cleaning pad mounted thereon. The rotary or linear actuator arm used to position the read/write head activates the ratchet mechanism. The ratchet mechanism rotates the cleaning pad while the actuator unloads the read/write head from the disk. A loading ramp is used to vertically position the read/write head relative to a cleaning surface of the cleaning pad. This conventional cleaning apparatus is more complicated in structure, lower in efficiency, and is

Application No.: 10/669,621
Amendment dated: October 25, 2005
Reply to Office Action dated: July 25, 2005

used only after assembly of a disk drive, making it unsuitable for use in the mass production of the heads.

SUMMARY OF THE INVENTION

[0008] A new kind of cleaning and polishing apparatus and method for cleaning the heads of a head gimbal assembly to eliminate contamination of the heads by dusts or particulates is disclosed. In accordance with one aspect of the present invention, a cleaning and polishing apparatus for cleaning a head may have a frame, a plurality of carriers for locating and holding a plurality of HGAs, a plurality of polish fingers under the carriers and fixed on a loading base, a cloth attached to said fingers, and a plurality of press-pins on each of the carriers. The HGAs may have a face and a slider with an air-bearing surface (ABS) to be polished and directed downwards. The cloth may act as a polish medium to provide a plurality of polish surfaces on which the HGAs are polished and cleaned. The press pins press on a HGA's flexure to provide proper friction between the slider ABS and the polish surface.

[0009] According to another embodiment, a pneumatic cylinder unit is combined with the carriers. The pneumatic cylinder unit, controlled by a programmable controller, may move the carriers, as well as the plurality of HGAs. The pneumatic cylinder unit may move back and forth in X and Y directions according to a customized program. The solution may be sufficiently agitated by the motion of a cylinder unit to promote dissolution action. Also, a polish tank containing a cleaning solution, may be provided on the top of the frame. The cleaning solution is recirculated through a pump and a filter canister with an effective filter

Application No.: 10/669,621
Amendment dated: October 25, 2005
Reply to Office Action dated: July 25, 2005

cartridge. The filter canister may filter off the insoluble, suspended contaminants and particles in the solution so that the slider ABS will not be re-contaminated. A thermostatically controlled strip heater may heat the solution to a desired working temperature. The contaminants may be scrubbed off into the solution through solubilization, emulsification, chemical action by a detergent, etc. The temperature, kind, and concentration of the chemical substance of said solution may be selected to achieve maximum cleaning effectiveness. The apparatus and method of the invention is suitable for the removal of dusts, oils, fingerprints, and other organic and inorganic contaminants in the form of both particulate and thin-film.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The above and other objects and advantages of the present invention will be described by way of preferred embodiments and with reference to the drawings, in which

Figure 1 is a top view of the polish cleaning apparatus of the present invention;

Figure 2 is a perspective view of an HGA carrier positioned on polish fingers in the polish cleaning apparatus of the present invention; and

Figure 3 is a diagram of water circulation of the polish cleaning apparatus.

DETAILED DESCRIPTION

[0011] The head gimbal assembly (HGA) is a kind of precision component in a disk drive. The conventional ultrasonic cleaning can cause mechanical damage under high ultrasonic power, which limits its application, and can not provide an adequate cleaning effect.

Application No.: 10/669,621
Amendment dated: October 25, 2005
Reply to Office Action dated: July 25, 2005

However, the new polish cleaning technology can effectively clean the head and does not cause side effects for HGA performance. Basically, the polish cleaning can remove all kinds of contaminants such as dust, particles, film, etc. Its removal efficiency can achieve up to 95% for all kinds of contaminants whether it's organic or inorganic, while the classical ultrasonic cleaning does only about 60% for small particles and is not efficient for other kinds of contaminants.

[0012] As shown in Figures 1-3, one embodiment of a polishing and cleaning apparatus of the present invention may have polish fingers, HGA carriers, a cylinder motion unit and an immersion polish tank.

[0013] In one embodiment of the present invention, the polishing and cleaning method may be a contact-cleaning process using a type of polyester cloth. The polyester cloth has good anti-static properties having less particles or even being particle-free and has good wear durability as a cleaning medium. A pneumatic cylinder unit may bring the HGA being polished and cleaned into the cleaning area. The pneumatic cylinder unit may move back and forth in both X and Y directions on a cloth-strip wrapped onto a set of polish fingers. The slider air bearing surface (ABS) is polished with a much higher cleaning efficiency (nearly 90%), as shown in Figure 1.

[0014] In one embodiment illustrated by Figure 2, cleaning units 1 and 8 may have two rows of polish fingers 2. On these two rows of polish fingers 2, a kind of anti-static polyester

Application No.: 10/669,621
Amendment dated: October 25, 2005
Reply to Office Action dated: July 25, 2005

cloth-strip is fixed smoothly by tension force to form a polish cleaning surface. A plurality of HGAs 1 may be positioned on the cleaning surface to be cleaned and polished effectively.

[0015] The HGA carriers hold a plurality of HGAs 1. The HGA carriers also position the plurality of HGA 1 by the co-ordination of the carriers and polish fingers, see Figure 2. The HGA carriers may have a plurality of cylindrical pressing pins to press on a HGA's flexure. The HGA carriers may move back and forth according to a computer program for substantially simultaneous polishing and cleaning.

[0016] In one embodiment, the cylinder motion units may each comprise an X-cylinder 4, 5 and a Y-cylinder 3, 6. The X-cylinder 4, 5 and Y-cylinder 3, 6 move back and forth in X or Y direction, according to a computer program customized in advance, and cause HGA carriers as well as the plurality of HGAs to move in both X and Y directions repeatedly.

[0017] In one embodiment illustrated in Figure 3, the HGA carriers containing the HGAs may be immersed into a polish tank containing a solution so that the HGAs can be cleaned and polished. The tank may have an overflow weir, a pump, and a filter canister. The filter canister may have a 0.2 micron filter cartridge for solution recirculating and filtering. The tank may also have a thermostatically controlled strip heater to heat the solution to a proper working temperature.

Application No.: 10/669,621

Amendment dated: October 25, 2005

Reply to Office Action dated: July 25, 2005

[0018] The cleaning function may have chemical and physical actions, as well as the polish cleaning. A cloth scrubbing action may be performed first. The moving cloth strip scrubs off contaminants on the dirty slider surface being cleaned. This action smashes the mass contaminants into tiny pieces.

[0019] The detergent dissolution action may be performed second. The contaminants scrubbed off may be placed into solution through solubilization, emulsification, chemical action by a detergent, etc. As in a conventional cleaning process, time, temperature, and kind and concentration of the detergent may be important parameters in achieving maximum cleaning effectiveness. Motion of the cylinder may provide sufficient agitation to promote dissolution action.

[0020] The filtration action may be performed third. A filter canister may filter off the insoluble, suspended contaminants and particles in solution in time. Otherwise, they may re-contaminate the products so that the latter must be cleaned again.

[0021] While the present invention has been described by way of the preferred embodiments, the foregoing described is in all aspects illustrative, not restrictive. It is obvious to a person skilled in this art that numerous variations and modifications can be devised without departure from the scope of the invention.